

No. Eye-02 Electrostatic Field Meter

- A hand-held measuring instrument enabling you to measure an invisible electrostatic charge condition or ion balance of the ionizer easily.
- Maximum value (peak value) / pause can be displayed.
- LED cross mark as an index for correct measurement distance.
- Equipped with a female thread for camera screws; using with a tripod or jig enables measurements in stable state. Also provided with a plate for ion balance measurements.
- LCD has backlight and provides a bright, easy-to-see display in low light.
- Provided with a soft housing carrying case.
- Compatible with ISO 9000 traceability. A calibration table and certificate can be issued.



Measurement of charged potential



Ion balance measurement

CE RoHS

Model No.	Measurement range		Measuring distance
	Static charge voltage measuring	Ion Balance voltage measuring	
Eye-02	±0~±1.50kV (LO range) ±1.0~±22.0kV (HI range)	0~±220V	25mm±0.5mm between charged (object and the Eye-02)
Power source	Weight		EDP No.
9V DC (006 battery 1 pce.)	170g: without Ion Balance plate 30g: Ion Balance plate		621603

Accessories: Ion Balance Plate×1, Ground Cord w/alligator clip×1, Carrying Case×1


No. SRC-01 Surface Resistance Checker NEW

- Surface resistance checker that facilitates the surface resistance measurement of floor, mat, desk and chair.
- Press and hold the measurement button switch, and the measurement value appears on the display. Automatic power off function is available.
- Voltage can be switched to measure a broad range of resistance values.
- Can measure temperature/humidity at the same time as the surface resistance value.
- Supplied with probes to measure "point-to-point resistance", "resistance to ground" and "volume resistance".
- Comes with a carrying case useful to carry all necessary items for measurement.




Accessories:

- Probe (outer diameter: about 066mm, about 2.3 kg): 2
- Curled cord for a body grounding (banana plugs at both ends): 1
- Curled cord for measurement for the point-to-point resistance and resistance to ground (banana plug/mono plug): 2
- Crocodile clip: 1
- Large crocodile clip: 1
- Stainless plate (185mm×100mm): 1
- Carrying case: 1
- 9V battery (006P type: manganese dry battery): 1
- Manuals




With a carrying case

Useful to carry all necessary items for measurement



Resistance between 2 points on a surface.

Resistance between a ground and a connecting point by a probe on a surface



Surface resistivity

Volume resistance

CE RoHS

Model No.	Measurement standard	Measurement range	Applied voltage
SRC-01	IEC61340-4-1 JIS-C2170	10 ³ ~10 ¹² Ω (Ω/sq)	10V (R<1.0×10 ⁶ Ω or Ω/sq) 100V (R≥1.0×10 ⁶ Ω or Ω/sq)
Power source	Weight		EDP No.
9V battery (006P type)	Main body: Approx. 340g (including battery) Total weight: Approx. 6.2kg (including carrying case)		621604

※A battery (accessory) is included as a sample. It may be out of use before the estimated number of use with one battery. Replace with a new one in this case.
※Calibration certificate can be issued as option (payable).